




## ANNOVEX

### Absolute pressure sensor/transmitter type GMA 08.12.xxx Absolute pressure monitor type GMA 08.12.xxx

-  I M1 Ex ia I Ma
- Absolute pressure measuring with pressure sensitive resistor bridge
- High accuracy of measurement by compensation of the prevailing temperature by microcontroller system
- Output range of the output signal is variable
- Illuminated four-digit display
- Adjustments or status enquiries by means of a press button unit or a magnetic pointer. The housing need not be opened
- Code lock to prevent unauthorized manipulation (can be switched off)
- Fault self diagnosis with alpha numeric display
- Test of the output signal by simulated pressure values
- Choice between normed analog or digital output signals (optional)
- Two built-in limit switches with optocouplers or relays in the monitor
- Audio visual alarm unit optional (Monitor)
- The sensor can be replaced on site
- Housing protection rating IP65, sensor protection rating IP 54

The economical, permanently installed pressure sensor/transmitter and pressure monitor are characterised by their stable measuring characteristics, simple and secure operation, robustness, low weight and compact construction.

These devices conform to the explosion protection rating of intrinsic safety „i“, category I M1 Ex ia I Ma. This means that this device can be used in the zone M1 of underground mines, even when unpermitted high concentrations of the methane gas are prevailing.

This certification conforms to the ATEX directive 2014/34/EU for devices and protective systems permitted for use in areas endangered by explosions.

The pressure monitor differs from the pressure sensor/transmitter because of an additional limit value unit which is equipped with optocouplers or relays.

The measurement of the absolute pressure in the sensor block is by means of a pressure sensitive resistor bridge sensor.

To increase the measurement accuracy, a microcontroller continuously compensates the prevailing temperature value.

A socket as tube connection is in the lower area of the housing. Other tube connections on request.

The operation of the device is very simple: The operator places a small magnetic press button unit on the device. The housing need not be opened. As an alternative he can also use a magnetic pointer. A four digit code which can be entered initially, protects against unauthorized changing of the set values.

A self monitoring microcontroller system not only processes the measurement values precisely, it also carries out the operator specific instructions such as the entry of the code, signal instructions and messages, analog and digital outputs and test functions etc. A four digit back lit graphic display shows the measured values in 12 mm high digits.

These devices are placed in a fibre reinforced resin housing (impact strength 7 Joule) and are to be connected by means of a plug-in connector. The sensor block with the pressure sensor is located next to the connector.



For the suspension of the device a steel hanger is attached. Holes on the back of the device permit a rigid mounting.

In addition, the pressure monitor can be equipped with an audio visual alarm unit for giving alarms in the monitored area.



**ANNOVEX**  
**Absolute pressure sensor/transmitter type GMA 08.12.xxx**  
**Absolute pressure monitor type GMA 08.12.xxx**

**Technical Data**

<b>Certification</b>	 DMT 03 ATEX E 065 X according to directive 2014/34/EU
<b>Zone, Explosion protection rating</b>	 I M1 Ex ia I Ma
Principle of measurement	Pressure sensitive resistor-measurement bridge
Gas entry	Socket as tube connection
<b>Range of measurement</b>	<b>0...2000 hPa, other ranges on request</b>
Error of measurement	±2%
Resolution	1 hPa
Measured value response time $t_{90}$	≤ 10 s
Maximum permitted overpressure	4000 hPa
Display sequence	0.5 s
Adjustment range of the device code	0000...9999
Supply voltage	9...16 V–
Current consumption	
Sensor/transmitter with 1 mA- or 15 Hz output	15 mA
Sensor/transmitter with 20 mA output	35 mA
Monitor with Optocouplers and 1 mA- or 15 Hz output	17 mA
Monitor with relays and 1 mA- or 15 Hz output	27 mA
Monitor with Optocouplers and 20 mA output	37 mA
Monitor with relays and 20 mA output	47 mA
Current consumption of the audio visual alarm unit	additionally 100 mA max.
<b>Frequency output</b>	
Frequency range	6...15 Hz, switchable to 5...15 Hz
Output range adjustable between	100...2000 hPa
Optocoupler output	max.: 30 V, 100 mA, 100 mW
<b>Current output (alternative to the frequency output)</b>	
Ranges and loads	0.1/0.2...1 mA / ≤200 Ω to 4...20 mA / ≤200 Ω
Output range adjustable from	100...2000 hPa
<b>Test function by simulated measured values</b>	10 decimal steps from the start to the final value of the range of the data transmission output
<b>Limit switch Alarm 1 and Alarm 2 (Monitor)</b>	
Setting range	10...2000 hPa
Optocoupler output (quiescent current principle)	max. 30 V, 100 mA, 100 mW
Relay output (quiescent current principle)	max. 30 V, 1 A, 30 W
<b>Audio visual alarm unit optional (Monitor)</b>	
Signal tone	Sweeping 2400-2850 Hz at 7 Hz
Sound intensity	max. 103 dB (1m)
Flashing light	10 red, ultra highbright, pulsed LEDs
Signal frequency Alarm 1, Alarm 2	0.5 Hz, 1 Hz
Surroundings temperature	-20°C...+60°C
Humidity, non condensing	0...99% rel.
Dimensions without hanger, without alarm unit	W 122 mm, D 90 mm, H 179 mm
Dimensions without hanger, with alarm unit	W 122 mm, D 90 mm, H 310 mm
Weight without alarm unit	2 kg
Type of protection	IP 65, Gas inlet port IP 54
Material	Polyester, surface resistance <10 <sup>9</sup> Ohm
Impact strength	>7 Joule
<b>Accessories to be ordered separately</b>	
Connecting cable	VDL 4, 20m, max. length 100 m ( $R_L \leq 7,8 \Omega$ )
Press button device	TAS 3
Subject to technical updates	

22-11